

technical specifications

Adestor - Adhesive Specifications

Supplier	Torraspapel, Spain	Site	Almazan Mill
Website	http://www.torraspapel.com/	Date	March 2008

Adestor is available in three high quality, versatile adhesives to suit almost any adhesive need. If you are using the adhesive on difficult or unknown surfaces, we recommend you trial the product before purchase. Simply contact your Focus Paper representative for samples.

Super Permanent

Type	Water Acrylic Emulsion	Application Temp	+5°C
Code	SP - 123	Range of Use	-20°C / +80°C

Adhesive with very high peel and tack characteristics, suitable for difficult surfaces such as wood, cardboard or plastic. Good performance when die cutting, matrix stripping and automatic labelling.

Available with Cast Coated, Vellum Laser, and Vinyl Face Stocks

Permanent

Type	Water Acrylic Emulsion	Application Temp	+5°C
Code	A - 251	Range of Use	-20°C / +80°C

General use permanent adhesive, suitable on a great number of substrates, including slightly rough and cylindrical surfaces. High speed matrix-stripping and automatic labelling. Excellent performance when guillotining.

Available with all face stocks.

Removable

Type	Water Acrylic Emulsion	Application Temp	+5°C
Code	RA - 678	Range of Use	-20°C / +80°C

Acrylic removable adhesive. Excellent results when removing adhesive, minimising adhesive residue. Trials are recommended before use on difficult or unknown surfaces.

Available with Cast Coated, and Vellum Laser Face Stocks



Melbourne
P: 03 9550 4000
F: 03 9550 4001

Sydney
P: 02 9636 5720
F: 02 9636 5791

Brisbane
P: 07 3267 6698
F: 07 3267 1157